

INDUSTRIAL FANS

Series CFH Heavy Duty Industrial Fan Heads



1 YEAR WARRANTY

Model	FAN RPM	TYPE	BLADE SIZE	MOTOR H.P.	AIRFLOW In CFM
CFH12-1	1725	STANDARD	12"	1/4	1800
CFH12-6	1075/860	TWO SPEED OSCILLATING	12"	1/3	1800
CFH12-8	1075/860	TWO SPEED	12"	1/4	1800
CFH16-1	1725	STANDARD	16"	1/4	3800
CFH16-6	1075/860	TWO SPEED OSCILLATING	16"	1/3	3300
CFH16-8	1075/860	TWO SPEED	16"	1/4	3300
CFH18-1	1725	STANDARD	18"	1/4	4800
CFH18-6	1075/860	TWO SPEED OSCILLATING	18"	1/3	4500
CFH18-8	1075/860	TWO SPEED	18"	1/4	4500
CFH20-1	1725	STANDARD	20"	1/3	7000
CFH20-6	1075/860	TWO SPEED OSCILLATING	20"	1/3	6700
CFH20-8	1075/860	TWO SPEED	20"	1/3	6700
CFH24-1	1725	STANDARD	24"	1/3	7900
CFH24-6	1075/860	TWO SPEED OSCILLATING	24"	1/3	7600
CFH24-8	1075/860	TWO SPEED	24"	1/3	7600
CFH30-6	1075/860	TWO SPEED OSCILLATING	30"	1/2	9400
CFH30-8	1075/860	TWO SPEED	30"	1/2	9400

Leader Fans Industrial Circulating Fans effectively cool large areas in factories, stores, offices, restaurants and other public places. They provide relief from summer heat economically by creating a gentle air movement. The most common use for circulating fans is to provide personnel and spot cooling in industrial and commercial buildings. Leaders circulating fans can also be the solution to problems such as heat stratification, dampness and general air stagnation.

Heavy Duty Industrial Circulating Fans (Heads Only)

Comes complete with OSHA guards and totally enclosed, ball bearing motors with automatic overload protection. Aluminum blades. CSA and UL approved.

Mounting Accessories

Leader Fan has various types of mounting configurations available. Choose from below the mounting accessory that best suits your requirements. The accessories shown here fit all sizes of fan heads in the Industrial fan line.


Dock Arm - Model DF36x36

- Designed to ventilate hard to reach loading and unloading areas.
- Provides fresh cooled air into trailers for maximum safety and productivity.
- Dual pivot arm.
- 68" of reach at full extension.
- 1/4" plate steel wall mounting plate.



Rolling Cart - Model CFRC

1" tubular frame with black powder coat finish. Fan head can be pivoted up or down and easily locked into any position. Light weight and easy to manoeuvre on two 6" wheels. 40" W x 22" D x 32" H (not including fan head) Note: Not for use with oscillating fan head.



Pedestal Base - Model CFKPB

Adjustable in height from 4 ft. to 7 ft. measured at motor shaft. Base can be anchored to floor for maximum safety. Fan head can tilt up or down on base.



Wall Bracket - Model CFWB

Ideal for wall or beam mounting. No floor space required. Fan head tilts up or down and swivels side to side on the wall bracket.



Counter Stand - Model CFCS

Ideal for bench or work station applications. Fan head tilts up or down on stand. 12" High measured at motor shaft.



Ceiling Mount - Model CFCM

Can be easily anchored to ceiling. 24" downrod length. Note: Not available for oscillating fans.